

**SPECIALTY  
COLLECTION**

—by Somerset™—



HICKORY NATURAL  
Hickory

HICKORY MOONLIGHT  
Hickory

HICKORY SPICE  
Hickory

HICKORY NUTMEG  
Hickory

MAPLE NATURAL  
Maple

MAPLE GREYSTONE  
Maple

MAPLE TUMBLEWEED  
Maple

APPALACHIAN HICKORY AND MAPLE  
ARE BEAUTIFUL ALTERNATIVES  
TO TRADITIONAL OAK FLOORING.



**S SOLID**  
3/4" thick, random lengths up to 6-1/2'  
WIDTHS: 2-1/4", 3-1/4", 4", 5"

**S SOLIDPLUS™ ENGINEERED**  
1/2" thick, 3mm thick solid sawn wear  
layer, 8-ply, random lengths up to 6-1/2'  
WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

02/14

# SPECIALTY: SOLID



Product:	Somerset <b>Specialty Collection</b> Solid Hardwood Flooring					
Species:	Hickory or Hard Maple					
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.					
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> Hickory: 3-1/4", 4", 5" Maple: 2-1/4", 3-1/4", 4", 5" <b>Lengths:</b> Random from 10" up to 6-1/2' (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>					
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal ( <a href="http://www.appalachianwood.org">www.appalachianwood.org</a> ). Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association.					
Profile:	Eased Edge, Eased End					
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish					
Colors:		<b>2 1/4" Width Strip</b>	<b>3 1/4" Width Strip</b>	<b>4" Width Plank</b>	<b>5" Width Plank</b>	<b>Species</b>
	Hickory Natural		PS314HCB	PP41HCB	PP51HCB	Hickory
	Hickory Moonlight		PS314HMLB	PP41HMLB	PP51HMLB	Hickory
	Hickory Spice		PS314HSPB	PP41HSPB	PP51HSPB	Hickory
	Hickory Nutmeg		PS314HNUB	PP41HNUB	PP51HNUB	Hickory
	Maple Natural	PS5101B	PS51401B	PP41MPB	PP51MPB	Hard Maple
	Maple Greystone	PS5121B	PS51421B	PP41GSMB	PP51GSMB	Hard Maple
	Maple Tumbleweed	PS5110B	PS51410B	PP41TUMB	PP51TUMB	Hard Maple
Gloss Level:	Semi Gloss					
Janka Hardness:	<b>Species</b>	<b>Lbs</b>				
	Hickory	1820				
	Hard Maple	1450				
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request					
Flame Spread:	Class C					
Installation:	Nail down, or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are printed on the bottom of each carton and available at <a href="http://www.somersetfloors.com">www.somersetfloors.com</a>					
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )					
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )					
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer					

# SPECIALTY: SOLIDPLUS™ ENGINEERED



Product:	Somerset <b>Specialty Collection</b> Solid <b>Plus</b> Engineered Hardwood Flooring			
Species:	Hickory or Hard Maple			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.			
Dimensions:	<b>Thickness:</b> 1/2"*; 3mm* thick solid dry sawn wear layer <b>Widths:</b> 3-1/4", 5" <b>Lengths:</b> Random from 10" up to 6-1/2' <small>*Nominal</small>			
Construction:	8-ply cross-grain engineered construction; 7-ply birch core.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>3 1/4" Width</b>	<b>5" Width</b>	<b>Wear Layer Species</b>	
	Hickory Natural	EP314SPHCE	EP512SPHCE	Hickory
	Hickory Moonlight	EP314SPHME	EP512SPHME	Hickory
	Hickory Spice	EP314HSPE	EP512HSPE	Hickory
	Hickory Nutmeg	EP314HNUE	EP512HNUE	Hickory
	Maple Natural	EP314SPMPE	EP512SPMPE	Hard Maple
	Maple Greystone	EP314SPMGE	EP512SPMGE	Hard Maple
	Maple Tumbleweed	EP314TUME	EP512TUME	Hard Maple
Gloss Level:	Semi Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Hickory	1820		
	Hard Maple	1450		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C; ASTM E84 Flame Spread Index - 138			
Formaldehyde Emissions:	ASTM D6007; BLQ (beneath limit of qualification - .008ppm)			
Critical Radiant Flux (CRF):	ASTME648 - Test in Progress			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are printed on the bottom of each carton and available at <a href="http://www.somersetfloors.com">www.somersetfloors.com</a>			
Maintenance:	Somerset Ultimate™ Wood Flooring Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			