Northern Leathers Premium Vinyl Leather Tile







PRODUCT SUBMITTAL

Proven Flooring Experiences

1. MANUFACTURER **Roppe Corporation**

1602 N. Union Street P.O. Box 1158

Fostoria, Ohio USA 44830-1158 t: (419) 435.8546 | tf: (800) 537.9527

f: (419) 435.1056

E-mail: sales@roppe.com | Internet: www.roppe.com



2. PRODUCT DESCRIPTION

Roppe Northern Leathers is designed for use in commercial and residential applications. It contains a 0.028" (28 mil) wear layer topped with C-Shield UV cured ceramic bead finish. The composition ensures a 100% recyclable product while consisting of 72% recycled materials. The addition of Nano-Silver particles in the wear layer reduces 99.9% of Staph and E. coli present within 24 hours.

Gauge: .120" (3mm)

Size: 18" x 18" (457.2 mm x 457.2 mm) Nominal Packaging: 16 pieces per Carton (35.95 sq. /ft. per

Carton)

Colors: 6 available

3. TECHNICAL DATA

Product Classification

- ASTM F 1700 Solid Vinvl Tile: Class III. Type B **Fire Testing Information**
- ASTM E 648, Critical Radiant Flux Class 1, > .45 W/cm²

General Performance Information

- ASTM C 1028, Slip Resistance > 0.60
- ASTM F 970, Static Load 2,000 PSI, < .005"
- ASTM F 925, Resistance to Chemicals No Change
- ASTM F 1514, Heat Stability of Color ΔE < 8 Avg
- ASTM F 1515, Light Stability of Color ΔE < 8 Avg
- ASTM F 1914, Residual Indentation 3.4%
- ASTM F 2199, Dimensional Stability < .020" / In ft

4. INSTALLATION

Read all literature concerning the product description, product limitations, substrate preparation, adhesive

information, adhesive application, product installation procedures and warranty before installation. Deliver all materials to the installation location in its original packaging with labels intact and remove any plastic stretch wrap and do not stack materials. Inspect all material for proper type and color prior to installation. Store products in a dry area protected from the weather on a smooth, flat, dry surface with temperatures maintained between 65° F (19° C) and 85° F (30° C).

Approved Adhesives

2600 Spray-Grip Adhesive for Vinyl Tile, 3600 Vinyl Tile & Tread Adhesive and/or 535U Two-Part Epoxy

5. MAINTENANCE

Refer to the Northern Leathers Maintenance information for detailed instructions available on the Roppe Website.

6. AVAILABILITY AND COST

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit www.roppe.com.

7. SAMPLES

Obtain samples by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

8. LIMITED WARRANTY

Limited One (1) Year Manufacturer's Warranty Limited Ten (10) Year Commercial Wear Warranty Limited Twenty (20) Year Residential Wear Warranty

For complete substrate preparation, installation, maintenance instructions and/or warranty please visit www.roppe.com

Attach Color Submittal Sample Here