

Characteristics	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and 5G Superior click system
Description	Plank Size 7" Wide x 48" Long (Registered & Embossed) Plank Size 8.86" Wide x 48" Long (Registered & Embossed)
Size / Thickness	6.5mm Total Thickness (5.0mm Core + 1.5mm IXPE + 0.5mm Wearlayer)
Quality	1st quality, natural color variation, free of structural defects
Installation	Click System - Floating
Warranty	Lifetime Residential Wear Warranty Lifetime Structural Warranty Limited Lifetime Waterproof Warranty 10 Year Limited Light Commercial Warranty
Wear Resistance (method A)	2100 cycles - Classification (Class 33)
Impact Resistance (Big Ball)	1800mm - Classification (Class 34)
Micro-scratch Resistance	MSR-A2; MSR-B1 - Classification (Class 34)
Castor Chair Resistance	25,000 cycles - Classification (34) No visible damage effects from furniture leg testing.
Approximate IIC Rating on 6" Thick Concrete Slab Floor (150 lbs/cu ft)	IIC: 52 - (IIC: 64 with drop ceiling) STC: 49 - (STC: 61 with drop ceiling)
Residual indentation (Big Ball impact)	0.02 - Classification (34)
Resistance to staining	No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H ₂ O ₂), shoe polish.
Peel Strenth ISO 24345:2006	Mean Value: MD 110 N/50mm; AMD 105 N/50mm
Fungi Resistance ASTM G21-15	Unlike Cork, this product shows zero "None" results for observed growth.
FloorScore®	SCS-FS-04026 2016.06.01 - 2017.05.31
Packaging	
Content of Box	(7" x 48" - 18.91Sq.Ft./ Box) & (8.86" x 48" - 17.73Sq.Ft. / Box)
Content of Pallet	(55 cartons - 2,211.02lbs - 7" Profile) & (56 cartons - 2,113.23lbs - 8.86" Profile)