



Description:	Pacifica Featuring COREtec® - Patented Premium Engineered Luxury Vinyl Plank Floating Floor with Attached Cork Underlayment
Warranty:	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 10 Year Limited Commercial Wear Warranty
Installation:	Float, Glue Down
Size/Packaging:	7.17" x 48.03" x 8 mm planks 38.24 sq. ft./carton, 16 planks per carton, 60 lbs. each carton, 35 ctns per pallet
Pattern Repeat:	5 planks
Construction:	1.7 mm virgin PVC (0.5 mm/20 mil wear surface) 4.8 mm COREtec® core 1.5 mm cork underlayment
Wear Finish:	UV-cured acrylic
Gloss Level:	6% - 10%

Test Data:

ASTM-E648 Critical Radiant Flux:	Meets or exceeds, Class 1
ASTM E492-09 Impact Sound Conduction:	IIC 62 db
ASTM E90-09 Airborne Sound Conduction:	STC 62 db
ASTM C518 Thermal Resistance:	R Value – 0.57
NALFA 3.2 Thickness Swell:	Class 4, Heavy Commercial
NALFA 3.3 Xenon Light Resistance:	Class 4, Heavy Commercial
NALFA 3.4 Cleanability-Stain Resistance:	Class 4, Heavy Commercial
NALFA 3.5 Large Ball Impact Resistance:	Class 4, Heavy Commercial
NALFA 3.6 Small Ball Impact Resistance:	Class 4, Heavy Commercial
NALFA 3.8 Dimensional Tolerance:	Class 4, Heavy Commercial
NALFA 3.9 Caster Chair:	Class 3, Commercial
NALFA 3.10 Surface Bonding:	1.31 N/mm – Exceeds Class 3 Commercial Requirement
ASTM C 1028-96 Static Coefficient of Friction:	0.68 (slip resistance) Passes ADA/OSHA standard
ASTM F-970-07 Static Load Limit:	0.004 inch – Passes at 250 psi
ASTM-F2753 Rolling Load Over Resilient FC:	0.024 inch
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Delta E Requirement
ASTM F 1515 Color Resistance to Light:	Meets <8.0 Delta E Requirement

Certifications:	CARB Phase 2 Compliant GREENGUARD GOLD Certified
------------------------	---

Environmental Statement: USFloors' commitment is to provide consumers and specifiers with beautiful and durable floors at a good value, while minimizing our impact on the environment and enhancing and improving it whenever possible. USFloors is a member of the USGBC.

Country of Origin: Manufactured in China